

(43) Date of A Publication 12.12.2001

(21) Application No 0013727.3

(22) Date of Filing 07.06.2000

(71) Applicant(s)
Frank Moeller
The Paddock, 182 Main Road, MILFORD, Stafford,
ST17 0UN, United Kingdom

(72) Inventor(s)
Frank Moeller

(74) Agent and/or Address for Service
Forrester Ketley & Co
Chamberlain House, Paradise Place, BIRMINGHAM,
B3 3HP, United Kingdom

(51) INT CL⁷
F16H 3/72

(52) UK CL (Edition S)
F2D DEC DE1 DE3 DE46 DE50 DE72 DE78 DE83 DE86

(56) Documents Cited
US 5730676 A US 5603671 A US 5577973 A
US 5558589 A

(58) Field of Search
UK CL (Edition S) F2D DEC
INT CL⁷ F16H 3/72
ONLINE: WPI; EPDOC; JAPIO.

(54) Abstract Title
Epicyclic transmission with electric motors to vary output speed

(57) An epicyclic transmission comprises a first annulus gear 26 grounded by a switched reluctance type first electric motor 13 and a second sun gear 18 grounded by a second motor 15 of the switched reluctance type. The transmission has control means which permits the speed of the motors 13, 15 to be varied so as to alter an output speed of the transmission. First annulus gear 26 is engaged with first planet wheels 24 having a first carrier that is connected to a second annulus gear 30. Second annulus gear 39 drives second planet wheels 31 having a second carrier which may be connected to an output shaft 37. The first carrier and first planet wheels 24 may be driven, via flywheel 22, by an input to the transmission. First planet wheels 24 also drive a first sun gear 19 which is coupled to the second sun gear 18.




FIG 1

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.




FIG 1




FIG 2




FIG 3

**Electric Power Split Transmission
Spread Sheet Model, 74 kW engine at 3200 RPM input**

Ro	-3.62	EP1	3.62	EP2	-2.15	0	2.15	3.15	engine
Pos	0	output	engine	output	sun speed	sun speed	carr.speed	ring	E2
					-710	-710	1959	3200	-710
RPM					sun torque	sun torque	carr.torque	ring	3200
					5	115	-361	246	221
Nm					sun power	sun power	carr. power	ring	net el.
					-0.4	-8.5	-74.0	82.5	0.0
kW					E1	E1	Output EP2	part engine	74
					Input EP1				

slider value
only
7280
ring speed
RPM slide
E1

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power, min output speed setting
max torque on E2 motor = 120 Nm
electric power flow 8.9 kW
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 1

Electric Power Split Transmission
Spread Sheet Model, 74 kW engine at 3200 RPM Input

Ro	-3.62	EP1	3.62	4.62	EP2	-2.15	2.15	3.15	engine
Pos	0	output	engine	ring	output	0	carr.speed	ring	
RPM	16008	sun speed	carr.speed	-338	7266	16008	3200	3200	3200
Nm	-33	sun torque	carr.torque	ring	carr.torque	31	ring	ring	221
kW	-56.0	sun power	carr. power	ring	carr. power	51.8	ring	ring	74
	E1	Input EP1	E2		Output EP2	E1	part engine		
									net el.
									0.0



slider value
only
2662
ring speed
RPM slide
E1

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power, max output speed setting
max electric motor speed = 16000 RPM
electric power flow 4.3 kW
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 2

Electric Power Split Transmission
Spread Sheet Model, 74 kW engine at 3200 RPM input

Ro	-3.62	EP1	3.62	engine	4.62	E1	Ro	-2.15	EP2	2.15	output	3.15	engine
Pos	0	output	engine	sun speed	carr.speed	ring	Pos	0	sun speed	carr.speed	ring	3200	3200
RPM	-4	sun torque	carr.torque	ring	4085	ring	RPM	-4	sun torque	carr.torque	ring	3200	3200
Nm	0	sun power	carr. power	ring	0.1	ring	Nm	103	sun power	carr. power	ring	221	221
kW	0.0	E1	Input EP1	E2	0.0	E2	kW	0.0	Output EP2	part engine	net el.	0.0	74

▲

slider value

only

7085

ring speed

RPM slide

E1

▼

▼

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power, first node point setting

no internal electric power flow
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 3

Electric Power Split Transmission
Spread Sheet Model, 74 kW engine at 3200 RPM Input

Ro	-3.62	EP1	3.62	engine	4.62	E1		Ro	-2.15	EP2	2.15	output	3.15		engine
Pos	0		output	engine	ring			Pos	0		output	ring			
RPM	14788	3200	sun speed carr.speed	3200	-1			RPM	14788	6879	3200	ring			
Nm	-33	151	sun torque carr.torque	ring	-118			Nm	33	-103	70	ring			
KW	-50.5	50.5	sun power carr. power	ring	0.0			KW	50.5	-74.0	23.5	ring			
	E1	Input EP1	E2						E1	Output EP2	part engine				

slider value
only
2999
ring speed
RPM slide
E1

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power, second node point setting

no internal electric power flow
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 4

Electric Power Split Transmission									
Spread Sheet Model, 74 kW engine at 3200 RPM Input									
Ro	-3.62	EP1	3.62	4.62	EP2	-2.15	0	2.15	3.15
Pos	0	output	engine	ring	output	sun speed	car. speed	ring	engine
RPM	5347	3200	2607	2607	3881	5347	3881	3200	3200
Nm	-21	97	-76	-75.7	-182	58	-182	124	221
kW	-11.7	32.4	-20.7	-20.7	-74.0	32.4	-74.0	41.6	74
	E1	Input EP1	E2	E1	Output EP2	E1	part engine	net el.	
								0.0	

slider value
only
5607
ring speed
RPM slide
E1

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power, max electric power between node points
(can be avoided by engine speed variation)
electric power flow = 20.7 kW
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 5

Electric Power Split Transmission
Spread Sheet Model, vehicle reversing, 4 kW engine input at 1000 RPM

Ro	-3.62	EP1	3.62	4.62	E1	Ro	-2.15	EP2	2.15	3.15	E2	engine
Pos	0	output	engine	ring	ring	Pos	0	output	output	ring	ring	engine
RPM	-5364	sun speed	carr.speed	1000	2758	RPM	-5364	sun speed	carr.speed	1000	-5364	1000
Nm	-14	sun torque	carr.torque	64	-50	Nm	-12	sun torque	carr.torque	-26	-25.7	38
KW	7.8	sun power	carr. power	6.7	-14.4	KW	6.7	sun power	carr. power	-2.7	14.4	4
	E1	Input EP1	E2				E1	Output EP2	part engine			

slider value
only
5758
ring speed
RPM slide
E1

EP1/2 = epicyclic stages
E1/2 = electric motors

Reverse speed setting at 1000 engine RPM

electric power flow = 14.4 kW
no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 6

Electric Power Split Transmission

Spread Sheet Model, vehicle stopped, engine speed Input at 1200 RPM

	Ro	-3.62	EP1		E1		Ro	-2.15	EP2		E2		engine
Pos	0	output	engine	ring	2246		Pos	0	output	ring	3.15		
RPM	-2587	sun speed	carr.speed	1200	2246	RPM		sun speed	carr.speed	1200	-2587		1200
Nm	0	sun torque	carr.torque	ring	0		Nm	0	sun torque	carr.torque	ring	0.0	0
kW	0.0	sun power	carr. power	ring	0.0		kW	0.0	sun power	carr. power	ring	net el. 0.0	0
	E1	Input EP1	E2				E1	Output EP2	part engine				

slider value

only

5246

ring speed

13

EP1/2 = epicyclic stages

E1/2 = electric motors

Zero vehicle speed setting, held by speed control of motors

1200 RPM engine speed

no power flow, if no losses are assumed

no electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 7

Electric Power Split Transmission

Spread Sheet Model, vehicle stopped, starting engine

Ro	-3.62	EP1	3.62	4.62	EP2	-2.15	0	2.15	3.15	engine
Pos	0	output	engine	ring	output	sun speed	carr. speed	ring		
RPM	-652	300	carr. speed	563	-2	-652	300	ring		300
Nm	14	-64	sun torque	50	0	0	0	ring		-64
kW	-0.9	-2.0	sun power	2.9	0.0	0.0	0.0	ring	net el.	-2
	E1	Input EP1	E2		E1	Output EP2	part engine			

slider value
only
3563
ring speed
RPM slide
E1



EP1/2 = epicyclic stages
E1/2 = electric motors

Zero vehicle speed setting, starting engine at 300 RPM and 2 kW starting load


2 kW electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 8

Electric Power Split Transmission
Spread Sheet Model, 74 kW engine at 3200 RPM + 10 kW electric from external source

Ro		EP1		EP2		E1		E2		engine	
Pos	-3.62	0	3.62	0	2.15	Pos	0	0	2.15	ring	3200
RPM	12525	output	3200	output	6160	RPM	12525	output	6160	ring	3200
Nm	-29	sun speed	132	sun torque	-103	Nm	41	sun torque	-130	ring	221
kW	-37.5	sun power	44.2	sun power	-6.8	kW	54.2	sun power	-84.0	ring	74
		Input EP1		Output EP2						net el.	



EP1/2 = epleycilic stages
 E1/2 = electric motors

Full power + 10 kW electric power from external source

highest electric motor power = 16.8 kW (motoring)
 10 kW electric power flow from external source

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 9

Electric Power Split Transmission

Spread Sheet Model, 74 kW engine at 3200 RPM - 10 kW electric to external source

Ro	-3.62	EP1	3.62	4.62	EP2	-2.15	0	2.15	3.15	engine
Pos	0	output	engine	ring	output	sun speed	carr. speed	ring	3200	3200
RPM	12525	3200	624	624	6160	12525	6160	ring	3200	3200
Nm	-33	153	-120	-120	-99	31	-99	ring	68	221
kW	-43.5	51.3	-7.8	-7.8	-64.0	41.3	-64.0	ring	22.7	74
	E1	Input EP1	E2		Output EP2	E1	part engine			

slider value	only	3624	ring speed	RPM slide	E1
--------------	------	------	------------	-----------	----

EP1/2 = epicyclic stages
E1/2 = electric motors

Full power - 10 kW electric power to external source

highest electric motor power = -7.8 kW (generating)
external electric power flow to external source = 10 kW

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 10

Electric Power Split Transmission Spread Sheet Model, 10 kW engine braking 3200 RPM									
Ro	-3.62	EP1	3.62	4.62	EP2	-2.15	0	2.15	3.15
Pos	0	output	engine	ring	output	sun speed	carr. speed	ring	engine
RPM	12525	3200	624	624	6160	12525	6160	3200	3200
Nm	4	sun torque	carr. torque	ring	sun torque	carr. torque	ring	ring	-30
kW	5.5	sun power	carr. power	ring	sun power	carr. power	ring	ring	net el.
	E1	Input EP1	E2	1.0	E1	Output EP2	part engine	-3.5	0.0
				1.0				-1.0	-10

slider value	only	3624	ring speed	RPM slide	E1
--------------	------	------	------------	-----------	----

EP1/2 = epicyclic stages
E1/2 = electric motors

10 kW engine braking

Internal electric power flow = 1 kW
no external electric power flow

Mechanical and electrical losses are not calculated in this spreadsheet

Fig 4 Sheet 11

Electric Power Split Transmission
Spread Sheet Model, 10 kW electric braking engine at 2000 RPM

Ro	-3.62	EP1	Ro	-2.15	EP2
Pos	0	output engine	Pos	0	output
RPM	13606	sun speed carr.speed ring	RPM	13606	sun speed carr.speed ring
Nm	-2	sun torque carr.torque ring	Nm	-5	sun torque carr.torque ring
kW	-3.5	sun power carr. power ring	kW	-7.6	sun power carr. power ring
	E1	Input EP1		E1	Output EP2 part engine

▲

slider value only

1794

ring speed

RPM slide

E1

▼

EP1/2 = epicyclic stages
E1/2 = electric motors

10 kW electric brake power to external source (regenerative or dump resistor)

Internal electric power flow = 1.1 kW
10 kW external electric power flow

Mechanical and electrical losses are not calculated in this spreadsheet


Fig 4 Sheet 12

[illegible]

ring speed
RPM slide
E1

**losses are not calculated
on this spreadsheet**

**Electric Power Split
Transmission** **Fig 5**



PATENTS ACT 1977

A10087GB-JNL/jm

Title: Single Regime Power Split Transmission

Description of Invention

This invention relates to a transmission in or for an automotive vehicle with at least two wheels and of up to approximately 5 tonnes gross weight. Such a transmission is referred to hereinafter as being of the kind specified.

An object of the invention is to provide a new and improved transmission of the kind specified.

According to the invention we provide a transmission of the kind specified comprising a first epicyclic train having a first carrier member, which carries at least one first planet member which is in driving engagement with a first annulus member and with a first sun wheel member and a second epicyclic train comprising a second carrier member, which carries at least one second planet member which is in driving engagement with a second annulus member and with a second sun wheel member wherein the first carrier member is connected to the second annulus member and the first and second sun wheel members being connected together, the first annulus is connected to ground through a first electric motor and the second sun wheel is connected to ground through a second electric motor, one of said members of the first train provides an input to said transmission and one of said members of the second train provides an output of said transmission and there being control means to permit the speed of said motors to be varied to vary the output speed of the transmission.

The first carrier of the first train may provide an input of the said transmission.

The second carrier of the second train may provide an output of said transmission.

The output of the transmission may be connected to the wheels of a vehicle.

The output of the transmission may provide an input to at least one other transmission.

The output of the other transmission or of at least one of the other transmissions may be connected to the wheels of a vehicle.

The output of the transmission or of the other transmission or of at least one of the other transmissions may be connected to the wheels of a vehicle via a clutch means and/or a differential means.

The first motor may comprise a rotor connected to the first annulus member and a stator connected to ground.

The first annulus member may be mounted to rotate fixedly with the rotor of the first motor.

The second motor may comprise a rotor connected to the second sun gear member.

The first sun member and the second sun member may be fixed to rotate with a shaft and the rotor of the second motor may also be adapted to rotate with said shaft.

The first sun member, second sun member and the rotor of the second motor may be longitudinally disposed on said shaft in said order.

Bearing means may be provided between the first carrier member and the first annulus member.

Alternatively, the first planet members and the first annulus member may be mutually supported by virtue of said interengagement therebetween.

All the interengaging members may comprise gear wheels.

Further alternatively, the first planetary members may comprise taper rollers in frictional engagement with said first annulus member and said first sun wheel member.

Biasing means may be provided to bias said planetary members into said frictional engagement and reaction means may be provided for said first annulus member and said first sun wheel member.

Each electric motor may be a switched reluctance motor.

The transmission may be a power split transmission in which means are provided to supply electrical power to one of said motors from the other of said motors.

As a result the transmission does not require any external electrical power supply.

The transmission may be provided with an electrical energy storage means in which electrical power generated by either of said motors is stored.

For example, when the transmission is operated at a relatively slow speed and/or the vehicle is braking an amount of electrical power is generated which is not required by either motor and this is stored in the energy storage means.

Power may be supplied from the energy storage means to at least one of said motors to limit variation in the amount of power supplied to one or other of said motors.

The input of the transmission may be connected to an engine such as an internal combustion engine or an electric motor or indeed any other type of prime mover. Alternatively the input may be connected to an output of any design form of transmission from a prime mover.

The output of the transmission may be connected to the wheels of a vehicle but may be connected into another transmission of any kind including, for example, another power split transmission. Any vehicle within which the transmission is provided may be provided with a plurality of transmissions according to the present invention.

Three embodiments of the invention will now be described by way of example with reference to the accompanying drawings wherein:-

Figure 1 is a diagrammatic representation of a first transmission embodying the invention,

Figure 2 is a diagrammatic representation of a second transmission embodying the invention,

Figure 3 is a diagrammatic representation of a third embodiment of the invention,

Figure 4 comprises twelve tables setting out details of the transmission described herein when connected to a prime mover comprising a 74 kilowatt internal combustion engine operating at 3200 rpm with the transmission set at the twelve different settings referred to in each sheet,

Figure 5 is a spreadsheet setting out how the figures shown in Sheets 1-12 of Figure 4 have been calculated, and

Figure 6 is a graphical illustration in which traction and efficiency are plotted against speed.

Referring now to Figure 1, a transmission is indicated generally at 10 and comprises a housing 11 which provides a ground.

Fixed to the housing 11 is a stator 12 of a first electric motor 13. In the present example, electric motor 13 is of the "switched reluctance" type. The housing 11 also has fixed thereto a stator 14 of a second electric motor 15 also of the "switched reluctance" type.

The housing 11 also carries, via a suitable bearing means 16a, a shaft 16 which is rotatable relative to the housing 11 and fixedly carries a rotor 17 of the motor 15, a second sun wheel member 18 and a first sun wheel member 19, each of which comprises a gear. In addition a bearing, not shown, is provided between an end part 20 of the shaft 16 and a recess 21 provided in a flywheel 22 of a prime mover. The flywheel 22 also provides a first carrier member having a plurality of shafts 23, three in the present example, on each of which a first planet member 24 is rotatably mounted by bearing means 25.

The planet members 24 comprise gears which are in mesh with an annulus member 26, which also comprise a gear, and thus the first annulus member 26, first planetary member 24 together with the first carrier member 23 and the first sun wheel member 19 provide a first epicyclic, gear, train 27.

The annulus member 26 fixedly carries a rotor 28 of the first electric motor 12. Suitable bearing means 29 are provided between the first annulus member 26 and the first carrier member 23.

The first carrier 23 is also connected to a second annulus member 30 which comprises a gear which is in mesh with the second planet members 31 carried by shafts 32 of a second carrier member 33.

The number of first planet members and second planet members although comprising three, in each case, in the present example may be less or more than this figure and either the same or a different number of planet wheels may be provided in each epicyclic train.

The planet members 31 comprises gears are also in mesh with the second sun, gear, member 18 and so the second annulus member 30, said planet member 31 and second sun wheel member 18 together provide a second epicyclic, gear, train 34.

The second carrier member 33 is provided with a set of gear teeth 35 which mesh with a gear 36 carried on a shaft 37 which is carried in bearings 38 carried by the housing 11.

An oil seal 39 is provided between the flywheel 22 and the housing 11. Similarly an oil seal 39a is provided between the housing 11 and the output shaft 37. The shaft 37 is connected, where desired, by a clutch to, for example, wheels or other item to be driven by the transmission and, if desired, in addition, or alternatively, at least one differential may be connected to the shaft 37.

In use, the flywheel 22 is driven by a prime mover which, for example, may be an internal combustion engine or may be of any other desired type

including for example an electric motor. The flywheel 22 is rotated either at a constant speed by the prime mover or the speed of the prime mover is varied so as to vary the speed of rotation of the flywheel. In either case the power provided to the first electric motor 13 from the second electric motor 15 or vice versa is varied as desired to achieve a desired torque split between the two differentials therefore providing a desired output speed of the shaft 37. The variation in the speed of the motors is preferably achieved by a suitable electronic controller programmed according to the desired output of the transmission.

No external electrical power is required to be supplied since electrical power generated by one of the electric motors by rotation of the rotor of the electric motor relative to the stator may be fed to the other electric motor so as to drive its rotor with the electrical power thus generated.

Referring now to Figure 2, in which the same reference numerals have been used as were used in Figure 1 for corresponding parts. This embodiment is similar to that shown in Figure 1 but differs from that shown in Figure 1 by virtue of the absence of a separate bearing means between the first annular member and the first carrier member 23. In this case the gears are manufactured accurately so that the gears interengage and act as a bearing means. In addition the first rotor 29 is symmetrically disposed relative to the stator 12 so as to avoid any axial loads. In addition, the planet members are equally spaced so that there are no offset loads to upset the balance.

In the embodiment shown in Figure 3, again the same reference numerals have been used to refer to corresponding parts as were used in Figure 1 but in this case instead of the first annulus member 26 being provided with teeth which engage with the teeth of the first planetary wheel members 24, which are themselves engaged with the first sun gear 19, the first annulus member, first planetary members and first sun wheel are formed as tapered rollers, which are axially forced into engagement to provide a frictional drive.

For this reason these components are indicated in Figure 3 by the same reference numbers as used in Figures 1 and 2 with the addition of a prime sign.

The required axial load is achieved by providing the Belleville washers indicated at 40 in Figure 3 which serve to urge the first planetary wheel members 24' to the right in Figure 3 and so cause frictional engagement between the first planetary wheel members 24' and the first annulus member 26' and the first sun wheel member 19' respectively. To accommodate the thrust thus provided by the Belleville washers 40, thrust bearing means 41, 42 are provided. In addition, because of built in non-symmetrical disposition of the stator and rotor 26, 28 on rotation additional magnetic loads which are torque dependent will be created which are supported by the thrust bearing means 43.

It should be noted that for starting the engine it is not necessary to disengage any clutches with which the engine may be provided since the electric motors can keep the vehicle stationary during the starting procedure. If a clutch is provided and if it is disengaged in an emergency then the electric motors can synchronise the relevant clutch halves for easy engagement.

In any of the embodiments described hereinbefore if desired energy storage means, for example a suitable battery, may be connected to at least one and preferably to both of the motors. As a result when the transmission is operated at a relatively slow speed and/or the vehicle is braking an amount of electrical power is generated and this is fed to and stored in the energy storage means.

Power may be supplied from the energy storage means to at least one of the motors to limit variation in the amount of power supplied to the other of said motors.

If desired electrical power may be supplied to other external means such as regenerative or dump resistor to assist in braking of the engine for example as shown in Sheet 12 of Figure 4.

It is important to maintain the power requirements of the electrical motors to a minimum to reduce cost and to increase transmission efficiency particularly as electrical control of motors can be expensive for high powers and the efficiency of motors and generators combined is not greater than for example 80% whereas mechanical efficiency can be as high as 97% for example.

The present invention provides a power shaft transmission which circulates relatively little electrical power, especially if the engine speed is always readjusted by the vehicle controller to run the transmission close to one of the electrical power node points. These node points occur, when one of the motors is at a standstill and therefore cannot generate nor absorb any power. This is the condition shown in Sheets 3 and 4 of Figure 4.

It will be clear to a person of skill in the art that for each different vehicle and engine combination the ratios of the transmission have to be adjusted to make the node points most effective.

In the present specification "comprise" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. A transmission of the kind specified comprising a first epicyclic train having a first carrier member, which carries at least one first planet member which is in driving engagement with a first annulus member and with a first sun wheel member and a second epicyclic train comprising a second carrier member, which carries at least one second planet member which is in driving engagement with a second annulus member and with a second sun wheel member wherein the first carrier member is connected to the second annulus member and the first and second sun wheel members are connected together, the first annulus is connected to ground through a first electric motor and the second sun wheel is connected to ground through a second electric motor, one of said members of the first train provides an input to said transmission and one of said members of the second train provides an output of said transmission and there being control means to permit the speed of said motors to be varied to vary the output speed of the transmission.
2. A transmission according to Claim 1 wherein the first carrier of the first train provides an input of the said transmission.
3. A transmission according to Claim 1 or Claim 2 wherein the second carrier of the second train provides an output of said transmission.
4. A transmission according to any one of the preceding claims wherein the output of the transmission is connected to the wheels of a vehicle.
5. A transmission according to any one of Claims 1 to 3 wherein the output of the transmission provides an input to at least one other transmission.

6. A transmission according to Claim 5 wherein the output of the other transmission or of at least one of the other transmissions is connected to wheels of a vehicle.
7. A transmission according to any one of Claims 4 to 6 wherein the output of the transmission or said other transmission or at least one of the other transmissions is connected to the wheels of a vehicle via a clutch means and/or a differential means.
8. A transmission according to any one of the preceding claims wherein the first motor comprises a rotor connected to the first annulus member and a stator connected to ground.
9. A transmission according to Claim 8 wherein the first annulus member is mounted to rotate fixedly with the rotor of the first motor.
10. A transmission according to any one of the preceding claims wherein the second motor comprises a rotor connected to the second sun gear member.
11. A transmission according to Claim 10 wherein the first sun member and the second sun member are fixed to rotate with a shaft and the rotor of the second motor is also adapted to rotate with said shaft.
12. A transmission according to Claim 11 wherein the first sun member, second sun member and the rotor of the second motor are longitudinally disposed on said shaft in said order.

13. A transmission according to any one of the preceding claims wherein bearing means are provided between the first carrier member and the first annulus member.

14. A transmission according to any one of Claims 1 to 12 wherein the first planet members and the first annulus member are mutually supported by virtue of said interengagement therebetween.

15. A transmission according to Claim 14 wherein all the interengaging members comprise gear wheels.

16. A transmission according to Claim 14 wherein the first planetary members comprise taper rollers in frictional engagement with said first annulus member and said first sun wheel member.

17. A transmission according to Claim 16 wherein biasing means are provided to bias said planetary members into said frictional engagement and reaction means may be provided for said first annulus member and said first sun wheel member.

18. A transmission according to any one of the preceding claims wherein each electric motor is a switched reluctance motor.

19. A transmission according to any one of the preceding claims wherein the transmission is a power split transmission in which means are provided to supply electrical power to one of said motors from the other of said motors.

20. A transmission according to any one of the preceding claims wherein the transmission is provided with an electrical energy storage means in which electrical power generated by either of said motors is stored.
21. A transmission according to Claim 20 wherein the power is supplied from the energy store to at least one of said motors.
22. A transmission substantially as hereinbefore described with reference to Figure 1 or Figure 2 or Figure 3 and Figures 4 to 6 of the accompanying drawings.
23. A transmission according to any one of the preceding claims wherein the transmission is connected to another transmission.
24. A transmission according to Claim 22 wherein said other transmission is of the same kind as the transmission claimed in Claims 1 to 22 is of a different kind.
25. Any novel feature or novel combination of features described herein and/or in the accompanying drawings.



Application No: GB 0013727.3
Claims searched: 1 to 24

Examiner: Mike McKinney
Date of search: 21 September 2001

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK CI (Ed.S): F2D (DEC).

Int CI (Ed.7): F16H 3/72.

Other: ONLINE: WPI; EPODOC; JAPIO.

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A	US 5730676 (SCHMIDT)	
A	US 5603671 (SCHMIDT)	
A	US 5577973 (SCHMIDT)	
A	US 5558589 (SCHMIDT)	

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

An Executive Agency of the Department of Trade and Industry